


semi-rotary drive DSM-8-90-P-FW

Part number: 185934

FESTO

With flanged shaft and fixed stop



Data sheet

| Feature | Value |
|------------------------------------|---|
| Size | 8 |
| Cushioning angle | 0.5 deg |
| Swivel angle | 0 ... 90 deg |
| Cushioning | P: Flexible cushioning rings/plates at both ends |
| Assembly position | Any |
| Mode of operation | double-acting |
| Design structure | Rotary vane |
| Position detection | No |
| Operating pressure | 3.5 ... 8 bar |
| Max. swivel frequency at 6 bar | 3 Hz |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (subsequently required for further operation) |
| Ambient temperature | 0 ... 60 °C |
| Theoretical torque at 6 bar | 0.35 Nm |
| Permissible mass moment of inertia | 0.0013 kgm ² |
| Product weight | 85 g |
| Mounting type | with internal (female) thread |
| Pneumatic connection | M3 |
| Materials note | Free of copper and PTFE Conforms to RoHS |
| Material of drive shaft | High alloy steel, non-corrosive |
| Material seals | TPE-U(PU) |
| Material housing | Aluminium Anodised |